



Garda Notifications are responsibility of contractor.
 Tower Lights to be provided by the Main Contractor.
 Management of pedestrians will be implement as required on site.
 Pedestrian barrier will be used when required.
 Safe passage through the site for emergency services will be facilitated.
 Where surfacing takes place the following may be used.
 *Ramps ahead 
 *Slippery road surface 

General Notes

SINGLE CARRIAGEWAY	
Traffic Signs Manual Chapter 8 / August 2019	
Speed Limit: 100km/h	
Temporary Signs	
Sign Visibility (m): 120	
Number of Signs: 4	
Cumulative Distance (m): 800	
Distance between signs (m): 200	
Min Size (mm): 750x750	
Minimum Rate of Taper	
Taper at Lane (m): 1 in 60	
Taper at Hard Shoulder (m): 1 in 30	
Maximum Lamp Spacing	
At Taper (m): 6	
Longitudinal (m) 24	
Maximum Cone Spacing	
At Tapers (m): 3	
Longitudinal (m): 12	
Cone Height (mm): 1000	
Safety Zone	
Longitudinal (m): 60	
Lateral (m): 1.2	
Design Parameters	
Road Level: 2	
Roadworks Type: A	
Min Lane Width (m): 3.0	
Additional Information	
If there is a Flagman at any entrance/business, ensure the Flagman sign is erected.	
If there is a minor road approaching the site use 25/50m spacing on that junction.	
Entrances/Businessess - use "Follow flow of Traffic" sign.	



Rev.	Description	Date

WEB TRAFFIC MANAGEMENT
 Tel: 061 600795, Fax: 061 397043, Mob: 087 7924216
 PATRICKSWELL, CO.LIMERICK.

PROJECT:
 N80_BALLICKMOYLER

CLIENT:
 ROADSTONE

DRAWN BY:
 LUIZ_ARLD

CHECKED BY:
 GERARD_MORAN

DESIGNER:
 IRENE_VALSH

Dwg. No. 081_01_RS_20	Rev. -
Date 11/08/20	
Scale NTS	