



General Notes

SINGLE CARRIAGEWAY
Traffic Signs Manual
Chapter 8 / August 2019

Speed Limit: 100km/h
Temporary Signs
Sign Visibility (m): 120
Number of Signs: 4
Cumulative Distance (m): 800
Distance between signs (m): 200
Min Size (mm): 750x750
Minimum Rate of Taper
Taper at Lane (m): 1 in 60
Taper at Hard Shoulder (m): 1 in 30
Maximum Lamp Spacing
At Taper (m): 6
Longitudinal (m): 24
Maximum Cone Spacing
At Tapers (m): 3
Longitudinal (m): 12
Cone Height (mm): 1000
Safety Zone
Longitudinal (m): 60
Lateral (m): 1.2
Design Parameters
Road Level: 2
Roadworks Type: A
Min Lane Width (m): 3.0
Additional Information
If there is a Flagman at any entrance/business, ensure the Flagman sign is erected.
If there is a minor road approaching the site use 25/50m spacing on that junction.
Entrances/Businessess - use "Follow flow of Traffic" sign.

Rev.	Description	Date

WEB TRAFFIC MANAGEMENT
Tel: 061 600795, Fax: 061 397043, Mob: 087 7924216
PATRICKSWELL_CO.LIMERICK.

PROJECT:
N80_OUGHAVAL

CLIENT:
ROADSTONE

DRAWN BY:
LUIZ_ARLD

CHECKED BY:
GERARD_MORAN

DESIGNER:
IRENE_VALSH

Doc. No.	13_RS_20	Rev.	—
Date	11/08/20		
Scale	NTS		