



General Notes

**SINGLE CARRIAGEWAY
50 OR 60km/h**

Speed Limit: 50 or 60km/h
Temporary Signs
Sign Visibility (m): 50
Number of Signs: 3
Cumulative Distance (m): 75
Distance between signs (m): 25
Min Size (mm): 600x600
Minimum Rate of Taper
Taper at Lane (m): 1 in 15
Taper at Hard Shoulder (m): 1 in 10
Maximum Lamp Spacing
At Taper (m): 6
Longitudinal (m): 12
Maximum Cone Spacing
At Tapers (m): 3
Longitudinal (m): 6
Cone Height (mm): 750
Safety Zone
Longitudinal (m): 25
Lateral (m): 0.5
Design Parameters
Road Level: 2
Roadworks Type: A
Min Lane Width (m): 3.0

Rev.	Description	Date

**WEB TRAFFIC
MANAGEMENT**

Tel: 061 600795, Fax: 061 397043, Mob: 087 792426
PATRICKSWELL_C@LIMERICK

PROJECT:
ROADWORKS
LP3811_HEALTH_SCHOOL_LA01S

CLIENT:
ROAD_STONE

DRAWN BY:
GERARD_MORAN
REVISED BY:
GERARD_MORAN
DESIGNED BY:
IRENE_WALSH

Doc No	087_02_RS_19	Rev.	-
Date	02/07/19		
Scale	NTS		