



General Notes

SINGLE CARRIAGEWAY
Traffic Signs Manual Chapter 8 / August 2019
Speed Limit: 80km/h
Temporary Signs
Sign Visibility (m): 90
Number of Signs: 4
Cumulative Distance (m): 480
Distance between signs (m): 120
Min Size (mm): 600x600
Minimum Rate of Taper
Taper at Lane (m): 1 in 40
Taper at Hard Shoulder (m): 1 in 40
Maximum Lamp Spacing
At Taper (m): 6
Longitudinal (m): 24
Maximum Cone Spacing
At Tapers (m): 3
Longitudinal (m): 12
Cone Height (mm): 750
Safety Zone
Longitudinal (m): 45
Lateral (m): 1.2
Design Parameters
Road Level: 2
Roadworks Type: A
Min Lane Width (m): 3.0
Additional Information
If there is a Flagman at any entrance/business, ensure the Flagman sign is erected.
If there is a minor road approaching the site use 25/50m spacing on that junction.
Entrances/Businesses - use "Follow flow of Traffic" sign.

Rev.	Description	Date

WEB TRAFFIC MANAGEMENT
 Tel: 061 680795, Fax: 061 337043, Mob: 087 792426
 PATRICKSWELL, CO. LIMERICK.

PROJECT:
 ROADWORKS
 R430_BURNTFURZE_LAOIS

CLIENT:
 ROADSTONE

DRAWN BY:
 LUIZ_AROLD

CHECKED BY:
 GERARD_MORAN

DESIGNER:
 IRENE_VALSH

Doc No	07_03_RS_21	Rev.	-
Date	07/05/21		
Scale	NTS		