



**General Notes**

**SINGLE CARRIAGEWAY**

Traffic Signs Manual  
Chapter 8 / August 2019

Speed Limit: 80km/h
Sign Visibility (m): 90
<b>Temporary Signs</b>
Number of Signs: 4
Cumulative Distance (m): 480
Distance between signs (m): 120
Min Size (mm): 600x600
<b>Minimum Rate of Taper</b>
Taper at Lane (m): 1 in 40
Taper at Hard Shoulder (m): 1 in 40
<b>Maximum Lamp Spacing</b>
At Taper (m): 6
Longitudinal (m) 24
<b>Maximum Cone Spacing</b>
At Tapers (m): 3
Longitudinal (m): 12
Cone Height (mm): 750
<b>Safety Zone</b>
Longitudinal (m): 45
Lateral (m): 1.2
<b>Design Parameters</b>
Road Level: 2
Roadworks Type: A
Min Lane Width (m): 3.0
<b>Additional Information</b>
If there is a Flagman at any entrance/business, ensure the Flagman sign is erected.
If there is a minor road approaching the site use 25/50m spacing on that junction.
Entrances/Businesses - use "Follow flow of Traffic" sign.

Rev.	Description	Date

**WEB TRAFFIC MANAGEMENT**  
 Tel: 061 600795, Fax: 061 337043, Mob: 087 792426  
 PATRICKSWELL\_CO.LIMERICK.

**PROJECT:**  
 ROADWORKS  
 R430\_BURNTFURZE\_LAOIS

**CLIENT:**  
 ROADSTONE

**DRAWN BY:**  
 LUIZ\_AROLD

**CHECKED BY:**  
 GERARD\_MORAN

**DESIGNER:**  
 IRENE\_VALSH

Des. No.	070_04_RS_21	Rev.	-
Date	07/05/21		
Scale	NTS		