



General Notes

SINGLE CARRIAGEWAY	
Traffic Signs Manual Chapter 8 / August 2019	
Speed Limit: 80km/h	
Temporary Signs	
Sign Visibility (m): 90	
Number of Signs: 4	
Cumulative Distance (m): 480	
Distance between signs (m): 120	
Min Size (mm): 600x600	
Minimum Rate of Taper	
Taper at Lane (m): 1 in 40	
Taper at Hard Shoulder (m): 1 in 40	
Maximum Lamp Spacing	
At Taper (m): 6	
Longitudinal (m) 24	
Maximum Cone Spacing	
At Tapers (m): 3	
Longitudinal (m): 12	
Cone Height (mm): 750	
Safety Zone	
Longitudinal (m): 45	
Lateral (m): 1.2	
Design Parameters	
Road Level: 2	
Roadworks Type: A	
Min Lane Width (m): 3.0	
Additional Information	
If there is a Flagman at any entrance/business, ensure the Flagman sign is erected.	
If there is a minor road approaching the site use 25/50m spacing on that junction.	
Entrances/Businesses - use "Follow flow of Traffic" sign.	

Rev.	Description	Date

WEB TRAFFIC MANAGEMENT
 Tel: 061 60795, Fax: 061 357043, Mob: 087 792426
 PATRICKSWELL, CO. LIMERICK.

PROJECT:
 ROADWORKS
 R430_BURNTFURZE_LAOIS

CLIENT:
 ROADSTONE

DRAWN BY:
 LUIZ_AROLD

CHECKED BY:
 GERARD_MORAN

DESIGNER:
 IRENE_VALSH

Doc No	070_02_RS_21	Rev.	-
Date	07/05/21		
Scale	NTS		