




Date: 29/01/2024 **Author:** THM/JC **Project:** KLS

Comments:
Traffic Management Plan to enable KLS with works on the R435 at Ballybrophy in Co. Laois.
Location 2



60km/h to 80km/h speed limit change

Roadworks End signage shall be placed 20m-50m after works







20.0 m

20.0 m

10.0 m

52.898852, -7.607527



Note 1:
Written dimensions are preferred, do not scale dimensions.
All dimensions to be checked before work commences and any discrepancies reported.
All traffic Management to be carried out in accordance with Chapter 8 of the Traffic Signs Manual in force at time of construction.

Note 2:
All signage to be erected outside visibility splays at junctions and site access.

Note 3:
Traffic Management will be audited and monitored in order to ensure safety and adequate traffic manoeuvrability. Should changes be required, drawings will be revised accordingly.

Note 4:
Interaction with local residents and landowners will be carried out by the main contractor.

Note 5:
All lighting requirements within the works area will be the responsibility of the main contractor.

Place advanced warning signage before brow of bridge for visibility

20.0 m

20.0 m

20.0 m

20.0 m

Legend

- Cone
- Lat. Safety Zone
- Long. Safety Zone
- Taper
- Works Area

Manifest

- 17 x Cone
- 8 x WK 001 Roadworks Ahead
- 5 x WK 061 Flagman Ahead
- 3 x P 010 End
- 3 x RUS 060 Stop and Go Disk - STOP
- 3 x RUS 061 Stop and Go Disk - GO
- 3 x WK 095 Stop Here on Red
- 2 x RUS 002 Keep Right
- 1 x P 003R Direction
- 1 x RUS 001 Keep Left
- 1 x W 185 Barrier Board

Table 1.1.1.4: Minimum Design Parameters for Level 1(iv) Roads Single Carriageway of 60km/h & Multi-lane / Dual ≤ 60km/h

Design Parameter	Type A > 12 hours	Type B < 12 hours	Type C < 15 mins
Advance Warning Signage			
Sign Size (mm)	600	600	-
Sign Visibility (m)	60	60	60
Number of Signs	3	2	-
Cumulative Distance (m)	60	40	-
Distance between Advance Warning Signs (m)	20	20	-
Taper			
Lane Taper Rate ^A	1 in 10	1 in 10	-
Hard Shoulder Taper Rate ^A	-	-	-
Transition Length (m)	2 x Taper Length	2 x Taper Length	-
Cones			
Cone Height (mm)	750	750	-
Taper Spacing (m) ^B	3	3	-
Longitudinal Spacing (m) ^B	6	6	-
Lamps (unlit areas only)			
Taper Spacing (m)	6	6	-
Longitudinal Spacing (m)	12	12	-
Safety Zones			
Longitudinal (m)	15	15	-
Lateral (m)	0.5	0.5	-
Lanes			
Lane Width (m) ^C	3 (2.5)	3 (2.5)	-
Two-way Roadway Width (m)	5	5	-

Notes:
A. 45° taper is required at shuttle traffic controlled layouts with cones at 1m centres
B. Cone spacing is the maximum permitted. Where geometry or any other site-specific reason dictates the spacing shall be reduced accordingly.
C. The optimum lane width for all classes of vehicles is 3.3m. This may be reduced to a minimum of 3m. Below this, HGVs and buses must be marshalled past the works. The absolute minimum lane width, if only cars and light vehicles are present, is 2.5m. See Section 0.4.3.4.