



General Notes

SINGLE CARRIAGEWAY 80 OR 100km/h
Speed Limit: 80 or 100km/h
Temporary Signs
Sign Visibility (m): 120
Number of Signs: 4
Cumulative Distance (m): 800
Distance between signs (m): 200
Min Size (mm): 600x600/750x750
Minimum Rate of Taper
Taper at Lane (m): 1 in 55
Taper at Hard Shoulder (m): 1 in 30
Maximum Lamp Spacing
At Taper (m): 6
Longitudinal (m): 12
Maximum Cone Spacing
At Tapers (m): 3
Longitudinal (m): 12
Cone Height (mm): 750
Safety Zone
Longitudinal (m): 60
Lateral (m): 1.2
Design Parameters
Road Level: 3/4
Roadworks Type: A
Min Lane Width (m): 3.0

Rev.	Description	Date

WEB TRAFFIC MANAGEMENT
 Tel: 061 680795, Fax: 061 397043, Mob: 087 7924216
 PATRICKSWELL_CDLIMERICK

PROJECT:
 ROADWORKS
 R445_BOLANDS_CROSS_JAMESTOWN
CLIENT:
 ROAD_STONE
DRAWN BY:
 GERARD_MORAN
REVISED BY:
 GERARD_MORAN
DESIGNED BY:
 IRENE_WALSH

Orig. No. 107_02_RS_19	Rev. -
Date 02/08/19	-
Scale NTS	-